

# Naked Container



**Concept:** Housing from insulated Sandwich elements.  
 2 compartments: Compartment 1 is tight and acts as a bund  
 Compartment 2 is the technical room with access door.  
 Integrated Anti freeze heating  
 Outside colour: white

Type	Volume	Length	Width	Height	Kg
BL-4000	4000	2860mm	1170mm	2320mm	700
BL-5000	5000	3370mm	1530mm	2317mm	750
BL-7500	7500	4600mm	1530mm	2317mm	980
BL-10000	10000	5820mm	1530mm	2317mm	1250

**Tank:** Installed into compartment 1  
 Type: Single wall  
 Material: Polyethylene  
 Sensor: Level sensor 4-20mA  
 Pump: Submersible pump type LEADER Ecodiver 1000A  
 or PETROTEC Submersible pump VN 3/4

**Filling point:** Filling Point in technical room.  
 Complete stainless steel piping circuit  
 2" dry coupling  
 Overfill protection plug type Fafnir  
 Level indicator integrated into electrical board or separated box  
 Optionals: Active overfill protection alarm with reset button

**Refuelling:** Standard foreseen for connexion to 1 satellite  
 Optionals: Multiple dispenser/satellite version (up to 4)  
 Timer function

Wireless communication: Endress & Hauser Fieldgate GSM (optional)

Electrical connections:  
 For non hazardous area  
 1 x 230VAC, 16A (3 x 2.5mm<sup>2</sup>)  
 EU Directive Low Voltage 73/23/EEG, updated 93/68/EEG



**Petrotec**



# Naked Container

PETROTEC Naked Container | Petrotec AdBlue Solutions



**Petrotec**



**Headquarters**  
 Parque Industrial de Guimarães, Pav. C2 / S. João de Ponte - 4805-661 GUIMARÃES - PORTUGAL  
 P. (+351) 253 479 300 F. (+351) 253 479 318  
 isd@petrotec.pt | www.petrotec.pt

